

## Op Amp Dual Low Offset Voltage Amplifier R-R O/P 5.5V 8-Pin SOIC Tube



Images are for reference only

[Inquiry](#)

**Manufacturer:** [Texas Instruments, Inc](#)

**Package/Case:** SOP8

**Product Type:** Amplifier ICs

**RoHS:** RoHS Compliant/Lead free 

**Lifecycle:** Active

### General Description

OPA336 series microPower CMOS operational amplifiers are designed for battery-powered applications. They operate on a single supply with operation as low as 2.1V. The output is rail-to-rail and swings to within 3mV of the supplies with a 100k load. The common-mode range extends to the negative supply—ideal for single-supply applications. Single, dual, and quad versions have identical specifications for maximum design flexibility.

In addition to small size and low quiescent current (20µA/amplifier), they feature low offset voltage (125µV max), low input bias current (1pA), and high open-loop gain (115dB). Dual and quad designs feature completely independent circuitry for lowest crosstalk and freedom from interaction.

OPA336 packages are the tiny SOT23-5 surface mount and SO-8 surface-mount. OPA2336 comes in the miniature MSOP-8 surface-mount, SO-8 surface-mount, and DIP-8 packages. The OPA4336 packages is the space-saving SSOP-16 surface-mount.

All are specified from -40°C to +85°C and operate from -55°C to +125°C. A macromodel is available for download (at [www.ti.com](http://www.ti.com)) for design analysis.

## Key Features

SINGLE-SUPPLY OPERATION

RAIL-TO-RAIL OUTPUT (within 3mV)

microPOWER:  $I_Q = 20\mu\text{A}/\text{Amplifier}$

micro SIZE PACKAGES

LOW OFFSET VOLTAGE: 125 $\mu\text{V}$  max

SPECIFIED FROM  $V_S = 2.3\text{V}$  to 5.5V

SINGLE, DUAL, AND QUAD VERSIONS

APPLICATIONS

BATTERY-POWERED INSTRUMENTS

PORTABLE DEVICES

HIGH-IMPEDANCE APPLICATIONS

PHOTODIODE PRE-AMPS

PRECISION INTEGRATORS

MEDICAL INSTRUMENTS

TEST EQUIPMENT

All trademarks are the property of their respective owners.

Description

OPA336 series microPower CMOS operational amplifiers are designed for battery-powered applications. They operate on a single supply with operation as low as 2.1V. The output is rail-to-rail and swings to within 3mV of the supplies with a 100k load. The common-mode range extends to the negative supply—ideal for single-supply applications. Single, dual, and quad versions have identical specifications for maximum design flexibility.

In addition to small size and low quiescent current (20 $\mu\text{A}/\text{amplifier}$ ), they feature low offset voltage (125 $\mu\text{V}$  max), low input bias current (1pA), and high open-loop gain (115dB). Dual and quad designs feature completely independent circuitry for lowest crosstalk and freedom from interaction.

OPA336 packages are the tiny SOT23-5 surface mount and SO-8 surface-mount. OPA2336 comes in the miniature MSOP-8 surface-mount, SO-8 surface-mount, and DIP-8 packages. The OPA4336 packages is the space-saving SSOP-16 surface-mount.

All are specified from  $-40^\circ\text{C}$  to  $+85^\circ\text{C}$  and operate from  $-55^\circ\text{C}$  to  $+125^\circ\text{C}$ . A macromodel is available for download (at [www.ti.com](http://www.ti.com)) for design analysis.

## Recommended For You

---

### OPA445BM

Texas Instruments, Inc

CAN

### OPA1611AIDR

Texas Instruments, Inc

SOP8

### OPA388QDBVRQ1

Texas Instruments, Inc

SOT23-5

### OPA2365AQDRQ1

Texas Instruments, Inc

SOP8

### OPA334AIDBVR

Texas Instruments, Inc

SOT23-6

### OPA2835IDGSR

Texas Instruments, Inc

MSOP10

**OPA656U**

Texas Instruments, Inc  
SOP8

**OPA360AIDCKR**

Texas Instruments, Inc  
SC70-6

**LMI11H/NOPB**

Texas Instruments, Inc  
CAN8

**OPA353UA**

Texas Instruments, Inc  
SOP8

**LMI3700MX/NOPB**

Texas Instruments, Inc  
SOP16

**OPA633KP**

Texas Instruments, Inc  
DIP8

**OPA453FAKTWT**

Texas Instruments, Inc  
TO263-7

**OPA4251UA**

Texas Instruments, Inc  
SOP14

**LMV321M5X/NOPB**

Texas Instruments, Inc  
SOT23-5