

TVS Diode Single Uni-Dir 100V 5KW 2-Pin Case P-600 T/R



Images are for reference only

[Inquiry](#)

Manufacturer: [Littelfuse Inc](#)

Package/Case: R-6

Product Type: Thyristors

Lifecycle: Active

General Description

The 5KP Series is designed specifically to protect sensitive electronic equipment from voltage transients induced by lightning and other transient voltage events.

Key Features

Halogen-Free and RoHS compliant

Typical maximum temperature coefficient $\Delta V_{BR} = 0.1\% \text{ } \Delta V_{BR} @ 25^{\circ}\text{C}$

Glass passivated junction

5000W peak pulse capability at $10\text{ }\mu\text{s}$ — $1000\text{ }\mu\text{s}$ waveform, repetition rate (duty cycles):0.01%

Fast response time: typically less than 1.0ps from 0 Volts to BV min

Excellent clamping capability

Low incremental surge resistance

Typical IR less than $2\text{ }\mu\text{A}$ above 12V

High temperature soldering guaranteed: $265^{\circ}\text{C}/10$ seconds/ $0.375\text{ }\mu\text{m}$, (9.5mm) lead length, 51bs., (2.3kg) tension

Plastic package has Underwriters Laboratory Flammability classification 94V-O

Matte Tin Lead-free plated

Recommended For You

5KP33A

Littelfuse Inc

R-6

5KP48CA

Littelfuse Inc

P-600

1.5KE18CA

Littelfuse Inc

DO-201AD

5KP33CA

Littelfuse Inc

R-6

15KPA48CA

Littelfuse Inc

R-6

1.5KE24A

Littelfuse Inc

DO-201AD

5KP24CA

Littelfuse Inc

R-6

1.5KE22CA

Littelfuse Inc

DO-201AD

1.5KE33A

Littelfuse Inc

DO-201

1.5KE43A

Littelfuse Inc

DO-201AD

5KP28A

Littelfuse Inc

R-6

1.5KE12A

Littelfuse Inc

DO-201

1.5KE27CA

Littelfuse Inc

DO-201

1.5KE75CA

Littelfuse Inc

DO-201AD

15KPA33A

Littelfuse Inc

R-6